TRINITY Tap Range Trinity 2 Bath Shower Mixer Chrome

TY2 BSM C



Features:

- Uniquely designed Timeless • detailing for traditional bathrooms.
- Hand-finished handles using precision watchmaker techniques.
- Metal fixing nut for added • durability

Product Certifications:





For more products, visit our website: ht



Specification				
Product Type:	Bathroom Taps			
Main Construction Material:	Brass			
Mount Type:	Deck Mounted			
Handle Type:	Crosshead			
Connection Inlet:	3/4" BSP Connections			
Connection Outlet:	Open			
Number of Tap Holes:	2			
Valve/Cartridge Type:	3/4" Compression Valves			
Plumbing System Requirements:	Suitable for all plumbing systems			
Working Pressure Range:	Min 0.2 bar, Max 5.0 bar			
Maximum Hot Water Temperature: °C	65			
Maximum Static Pressure: (bar)	10			
Flow Type:	Single			
Isolation Included:	No			

Dimensions (measurements in mm)





http://www.bristan.com	Flow Rates (I/min)							
化碱洗纸	System Pressure (bar)	0.2	0.5	1	2	3	5	
	Through Bath Filler	32	50.6	71.6	101.2	123.9	160	
	Through Handset	4.7	7.4	10.5	14.9	18.2	23.5	
TECHNICAL DATA SHEET	OF QUALIA YEAR TEO AMANTEO		В	RIS	STZ TAPS 8		RS D2	

Bristan, Birch Coppice Business Park, Dordon, Tamworth, B78 1SG. Telephone: 0844 701 6274. Facsimile: 0844 701 6275. Web Site: www.bristan.com Email: enquire@bristan.com The information contained on this page was correct at date of issue. Fitting Dimensions are provided as a guide only. Some variation may occur due to manufacturing tolerances. Bristan pursues a policy of continuing improvement in design and performance of its products and so reserves the right to change specifications without prior notice.