

Mira Coda Pro ERD

Mixer Shower



SUITABLE FOR ALL SYSTEMS



5 YEAR WARRANTY

Thermostatically controlled, safer showering with a sleek, chrome finish. Easily divert between the deluge showerhead and separate handshower.

Product Information

Description	Colour	Product No.
Mira Coda Pro ERD	Chrome	1.1836.006

Features & Benefits

Temperature control

Thermostatic temperature stability

Easy to fit

Front of tile installation system

Easy to service

Large, long-life filters and replaceable cartridge

For your customer

Separate flow and temperature controls

Maximum temperature stop for increased safety (with override for a hotter shower)

Mira Cool Shield™ to ensure valve doesn't get hot during showering

Mira Magni-flo™ technology delivers up to 3x more flow, even at low pressure

Integrated diverter allows you to easily divert between the deluge head and the handshower

1 spray 20cm deluge head with rub-clean nozzles plus separate 9cm showerhead



Product Specification

Tech Details

Temperature control

Control type: Thermostatic

Adjustable maximum temperature for on-site conditions

Installation

Water entry points: rear only

Inlet connections: 15 mm compression joints with pipes, 3/4" connection to valve

Outlet connections: 1/2" BSP Male Flat Face

Reversed inlets supported: No = hot left, cold right only

Supply Conditions (hot and cold)

Cold water range: Up to 25°C

Hot water range: 50°C-85°C (operating)
55°C-65°C (recommended)

Minimum maintained pressure: 0.1 bar (1 metre head)

Maximum maintained pressure: 5.0 bar (50 metre head)

Maximum static pressure: 10.0 bar (100 metre head)

Performance

Flow rate (at handset): 7.9 l/min at 0.5 bar

Flow rate (at overhead): 8.4 l/min at 0.5 bar

Temperature stability: ± 2°C

Safety Features

Automatic shutdown: Shutdown within 2 secs

Factory set to safe max temp: Factory set to 41°C

Adjustable maximum temperature for on-site conditions

Dimensions

