

shower valves - **CoolFlow Safe Touch Thermostatic Bar Shower**

thermostatic technology
which provides **total control**



CoolFlow safe touch thermostatic
bar shower
with flexible slide rail kit
ST20017CP

Introduction

The Coolflow bar shower from inta delivers safe hot water to enable you to shower whilst the main body remains cool to touch preventing unnecessary burns when in use.

- Suitable for use with unvented supplies, combi boilers, gravity and mains pressure systems
- Thermal cartridge technology
- Temperature stability of $\pm 2^{\circ}\text{C}$
- Fail safe protection on both the hot and cold supplies
- Operating pressure range of 0.2 to 5 bar
- Safe touch body

Product Range

Description	Code
CoolFlow safe touch thermostatic bar shower with flexible slide rail kit	ST20017CP
CoolFlow safe touch thermostatic bar shower	ST20015CP
Flexible slide rail kit	31665CPA

shower valves - CoolFlow Safe Touch Thermostatic Bar Shower

Features

Technical Specification

Max Inlet Pressure (static)	5 Bar
Min Inlet Pressure (dynamic)	0.2 Bar
Max Inlet Temperature	85°C
Factory Pre-set Temperature	38°C with max temp stop
Inlet Connections	G 3/4" F BSP (valve body)
Outlet Connections	G 1/2" BSP
Min Temperature differential to achieve hot or cold failsafe	15°C
System Installation: Unvented, Pressurised, Gravity and Combination Boilers	

