

**DECLARATION OF PERFORMANCE**  
**In accordance with annex III of Regulation (EU) 305/2011**

**No. BAL055-CPR/2013**

1. Unique identification code of the product-type:  
**BAL Tank-it**
2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):  
**See batch number and date of manufacture on packaging**
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

**Liquid-applied water impermeable product for external installations on walls and floors, beneath ceramic tiling (bonded with C2 adhesive in accordance with EN 12004).**

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant Article 11(5):

**Building Adhesives Limited,  
Newstead Industrial Estate,  
Longton Road,  
Trentham,  
Stoke on Trent,  
Staffordshire,  
ST4 8JB**

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

**Not applicable**

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

**System 3**

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

**EN 14891:2012**

**The Notified Body 0370 carried out the determination of the product type on the basis of type testing on samples taken by Building Adhesives Limited under System 3 and issued the test report 14/8281-492.**

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:


**Not applicable**

9. Declared performance

Essential characteristics	Performance	Harmonised technical specification
Initial tensile adhesion strength	$\geq 0.5\text{Nmm}^{-2}$	EN 14891:2012
Tensile adhesion strength after water contact	$\geq 0.5\text{Nmm}^{-2}$	
Tensile adhesion strength after heat ageing	$\geq 0.5\text{Nmm}^{-2}$	
Tensile adhesion strength after contact with lime water	$\geq 0.5\text{Nmm}^{-2}$	
Water impermeability	No penetration	
Crack bridging ability in standard conditions	$\geq 0.75\text{mm}$	
Crack bridging ability at low temperatures	$\geq 0.75\text{mm}$	
Tensile adhesion after freeze/thaw cycles	$\geq 0.5\text{Nmm}^{-2}$	
Tensile adhesion after contact with chlorinated water	$\geq 0.5\text{Nmm}^{-2}$	
Release of dangerous substances	See SDS	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by: David Longwell – Technical Manager



Stoke on Trent 09/07/2015