GRUNDFOS DATA SHEET

STR2 & SSR2 Universal Head Shower Booster Pump Range





General Description

The STR2 & SSR2 range of shower booster pumps has been specifically designed to minimise turbulence within the pump head, giving performance with low noise. The quiet AC induction motor is smooth and reliable, and the regenerative design of impeller is ideal for overcoming air pockets that can be generated in a shower system. This type of pump is ideal where the plumbing route includes multiple bends and elbows. All variants are fitted with high quality shaft seals, and supplied with high quality braided connection hoses and filter washers.

Choose the Universal type pump for installations where the outlet is at the same height, or above the water storage tank. The pump will switch on automatically when the outlet is opened.

Choose from 1.5 bar and 2.0 bar pressure twin ended and 2.0 bar pressure single ended pumps.

Features


- Continuously rated pump
- Regenerative impeller design
- IPX2 water ingress protection
- Auto-resetting thermal cutout
- Anti-vibration feet
- Mains connection lead 1.5m long
- Braided connection hoses with ¾" BSP pipe connections
- 2 year warranty

Technical Data

	Pump type		
- Data	STR2-1.5 CN Twin ended pump	STR2-2.0 CN Twin ended pump	SSR2-2.0 CN Single ended pump
Supply voltage		230 V, 50 Hz	
Power consumption	340 W	420 W	280 W
Rated current	1.5 A	1.8 A	1.2 A
Rating	Continuous operation *		
Enclosure class	IPX2 **		
Motor	AC induction		
Inlet head (min max.)		1 to 8 m	
Max. developed pump head	15 m	20 m	20 m
Max. operating pressure	3 bar	3 bar	3 bar
Min. starting flow	0.5 l/min.		
Length	310 mm	310 mm	215 mm
Width	235 mm	235 mm	200 mm
Height	255 mm	255 mm	246 mm
Weight	6 kg	6 kg	4.6 kg
Noise level	From 55 to 65 dB(A) @1m		

^{*} Recommended minimum flow rate: 5 l/min.

^{**} When mounted on a horizontal surface



Pump performance at 230V with 2m inlet head

Grundfos (Ireland) Ltd., Unit A, Merrywell Business Park, Ballymount Road Lower, Dublin 12.

Tel.: 01-4089800. Fax: 01-4569459. E-mail: salesireland@grundfos.com

ML10678 05/17

