

No. 001BS-PRBR/09-06-2021

1. *Unique identification of the product type (type, batch, serial number or any other element allowing identification of the product)*

Dry pressed ceramic tiles, with water absorption $0.5\% < E \leq 3\%$

2. *Intended use(s):*

For internal floorings and walls

3. *Name or registered trade mark, and contact address of the manufacturer:*

Argenta Cerámica S.L. , Pol. Ind. Vall d'Alba vial 5 parcela 2, 12194 Vall d'Alba (Castellón) España

4. *System of assesment and verification of constancy of performance (AVCP):*

System 4

5. *Name and identification number of notified laboratory, if relevant (Task(s) carried out, AVCP system, Document issued and data of issue.*

Don't apply

6. *Declared Performances:*

<i>Essential Characteristics</i>	<i>Performance</i>	<i>Harmonized Technical specifications</i>
Reaction to fire	A1/A1 _{FL}	BS EN 14411
Breaking strength	> 1100 N	
Tactility	NPD	
Slipperiness	NPD	
Bond strength: <i>Cementitious adhesive, type C2</i>	> 1 N/mm ²	
Release of dangerous substances	NPD	
Durability for: <i>Internal uses</i>	Pass	

- *The performance of the product identified in point 1 are in line with the declared performance in point 6*
- *This declaration of performance is issued under the sole responsibility of the manufacturer stated in point 3*

Signed for and on behalf of the manufacturer by:

Gonzalo Ramos–Quality Manager

Signature:



Place and date of issue:

Vall d' Alba, 9th of June 2021

No. 002BS-G/09-06-2021

1. *Unique identification of the product type (type, batch, serial number or any other element allowing identification of the product)*

Dry pressed ceramic tiles, with water absorption $3\% < E \leq 6\%$

2. *Intended use(s):*

For internal floorings and walls

3. *Name or registered trade mark, and contact address of the manufacturer:*

Argenta Cerámica S.L. , Pol. Ind. Vall d'Alba vial 5 parcela 2, 12194 Vall d'Alba (Castellón) España

4. *System of assesment and verification of constancy of performance (AVCP):*

Sistema 4 / System 4

5. *Name and identification number of notified laboratory, if relevant (Task(s) carried out, AVCP system, Document issued and data of issue.*

No aplica / Don't apply

6. *Declared Performances:*

<i>Essential Characteristics</i>	<i>Performance</i>	<i>Harmonized Technical specifications</i>
Reaction to fire	A1/A1 _{FL}	BS EN 14411
Breaking strength	> 1100 N	
Tactility	NPD	
Slipperiness	NPD	
Bond strength: Cementitious adhesive, type C1 Cementitious adhesive, type C2	> 0.5 N/mm ² > 1 N/mm ²	
Release of dangerous substances	NPD	
Durability for: Internal uses	Pass	

- *The performance of the product identified in point 1 are in line with the declared performance in point 6*
- *This declaration of performance is issued under the sole responsibility of the manufacturer stated in point 3*

Signed for and on behalf of the manufacturer by:

Gonzalo Ramos—Quality Manager

Signature:



Place and date of issue:

Vall d' Alba, 9th of June, 2021

No. 003BS-A/09-06-2021

1. *Unique identification of the product type (type, batch, serial number or any other element allowing identification of the product)*

Dry pressed ceramic tiles, with water absorption $E > 10\%$

2. *Intended use(s):*

For internal walls

3. *Name or registered trade mark, and contact address of the manufacturer:*

Argenta Cerámica S.L. , Pol. Ind. Vall d'Alba vial 5 parcela 2, 12194 Vall d'Alba (Castellón) España

4. *System of assesment and verification of constancy of performance (AVCP):*

System 4

5. *Name and identification number of notified laboratory, if relevant (Task(s) carried out, AVCP system, Document issued and data of issue.*

Don't apply

6. *Declared Performances:*

Essential Characteristics	Performance	Harmonized Technical specifications
Reaction to fire	A1	BS EN 14411
Bond strength: Cementitious adhesive, type C1 Cementitious adhesive, type C2	> 0.5 N/mm ² > 1 N/mm ²	
Release of dangerous substances	NPD	
Durability for: Internal uses	Pass	

- *The performance of the product identified in point 1 are in line with the declared performance in point 6*
- *This declaration of performance is issued under the sole responsibility of the manufacturer stated in point 3*

Signed for and on behalf of the manufacturer by:

Gonzalo Ramos–Quality Manager

Signature:

Place and date of issue:

Vall d' Alba, 9th of june, 2021



No. 004BS-PR/09-06-2021

1. *Unique identification of the product type (type, batch, serial number or any other element allowing identification of the product)*

Dry pressed ceramic tiles, with water absorption $E \leq 0.5\%$

2. *Intended use(s):*

For internal and external floorings and walls

3. *Name or registered trade mark, and contact address of the manufacturer:*

Argenta Cerámica S.L. , Pol. Ind. Vall d'Alba vial 5 parcela 2, 12194 Vall d'Alba (Castellón) España

4. *System of assesment and verification of constancy of performance (AVCP):*

System 4

5. *Name and identification number of notified laboratory, if relevant (Task(s) carried out, AVCP system, Document issued and data of issue.*

Don't apply

6. *Declared Performances:*

<i>Essential Characteristics</i>	<i>Performance</i>	<i>Harmonized Technical specifications</i>
Reaction to fire	A1/A1 _{FL}	BS EN 14411
Breaking strength	> 1300 N	
Tactility	NPD	
Slipperiness	NPD	
Bond strength: Cementitious adhesive, type C2	> 1 N/mm ²	
Release of dangerous substances	NPD	
Thermal shock resistance	Pass	
Durability for: Internal uses External uses: Freeze thaw resistance	Pass	

- *The performance of the product identified in point 1 are in line with the declared performance in point 6*
- *This declaration of performance is issued under the sole responsibility of the manufacturer stated in point 3*

Signed for and on behalf of the manufacturer by:

Gonzalo Ramos–Quality Manager

Signature:



Place and date of issue:

Vall d' Alba, 9th of June, 2021

No. 005BS-PRLAM/09-06-2021

1. *Unique identification of the product type (type, batch, serial number or any other element allowing identification of the product)*

Dry pressed ceramic tiles, with water absorption $E \leq 0.5\%$ and thickness $< 7.5\text{mm}$

2. *Intended use(s):*

For internal and external floorings and walls

3. *Name or registered trade mark, and contact address of the manufacturer:*

Argenta Cerámica S.L. , Pol. Ind. Vall d'Alba vial 5 parcela 2, 12194 Vall d'Alba (Castellón) España

4. *System of assesment and verification of constancy of performance (AVCP):*

Sistema 4 / System 4

5. *Name and identification number of notified laboratory, if relevant (Task(s) carried out, AVCP system, Document issued and data of issue.*

Don't apply

6. *Declared Performances:*

<i>Essential Characteristics</i>	<i>Performance</i>	<i>Harmonized Technical specifications</i>
Reaction to fire	A1/A1 _{FL}	BS EN 14411
Breaking strength	> 700 N	
Tactility	NPD	
Slipperiness	NPD	
Bond strength: Cementitious adhesive, type C2	> 1 N/mm ²	
Release of dangerous substances	NPD	
Thermal shock resistance	Pass	
Durability for: Internal uses External uses: Freeze thaw resistance	Pass	

- *The performance of the product identified in point 1 are in line with the declared performance in point 6*
- *This declaration of performance is issued under the sole responsibility of the manufacturer stated in point 3*

Signed for and on behalf of the manufacturer by:

Gonzalo Ramos –Quality Manager

Signature:

Place and date of issue:

Vall d' Alba, 9th of June, 2021

